

LUMINOS XTRA Technical Specification **Product Description** EarthPaint Luminos Xtra is a solvent-free, odourless, high performance, and highly washable emulsion paint for interior use. **Advantages** · Highly washable · Cover hair-line cracks · Long lasting • High coverage power · Excellent stain removal Odourless Exremely low dirt retention Where to use For use on new or previously painted interior surfaces such as plaster, cement, brick and renderings. Finish Smooth semi-matte Packaging 15L EarthPaint Colour Chart (custom colors available upon request) Colours Coverage Approximately 10-14m² /L per coat **Drying Time** For single coat Touch Dry 30 minutes Recoat 4 hours (Drying time varies depending on temperature and humidity level) Type of Binder Acrylic copolymer in aqueous dispersion Viscosity UNI 8902: 32000 ± 3200 cps at 25°C VOC < 10 mg/kg Free Formaldehyde < 10 mg/kg **Dirt Retention** UNI 10792: Low Gloss UNI 10795: Very Matte UNI 10560: >5000 psd, highly washable Washability Protect from frost and direct sunlight, the product has a shelf life Storage of 12 months if unopened and stored in dry and cool places. **Application Procedure** Surface Preparation Surfaces should be thoroughly cleaned and dried prior to application. Remove all loose material and dirt, fill in defects if any with proper filler. If the surface presents a difficult adherence, first apply Luminos Primer.

	Luminos Xtr
	TECHNICAL SPECIFICATION
Application	Apply by brush, roller, or spray. At least two coats.
Thinning Brush Roller	40-50% 15%
Spray gun	Varies depending upon tools and operating pressure used.
Recommendations	 Stir thoroughly before use. Thin with clean water. Do not over dilute. Do not paint with temperature below +5°C or above +35°C. Do not apply in direct sunlight or when relative humidity exceeds 80%. Do not wash the surface until after 20 days. Recommend to use opened paint quickly.
Safety Instructions	 EarthPaint Luminos is not considered as dangerous or hazardous according to the current norms. The usual precautions taken when handling chemical products are recommended. Contains no added lead or mercury. Non-flammable.

WARNING
Although the information contained herein is, to the best of our knowledge and experience, true and reliable, it must be taken as merely indicative and subject to confirmation after long-term practical applications. Therefore, anyone
who intends to use the product must ensure prior to usage that it is suitable for the envisaged application. In every care, the user alone is fully responsible for any consequences deriving from the use of the product. No warranty is
given or implied in connection with any recommendations or suggestions made by us or our representatives as the conditions of use and any labour involved are beyond our control.