



## MARMORIO ANTICO

### TECHNICAL SPECIFICATION

#### Product Description

**EarthPaint Marmorio Antico** is a mineral wall coating for internal and external use. The resulting effect is that of the traditional travertine marble finish. It is formulated to have a high degree of water vapor permeability and strong resistance to atmospheric agents.

#### Application

**EarthPaint Marmorio Antico** can be applied on walls, ceilings, soffits and special decorative features. It is recommended for both interior and exterior environments and is compatible with most plaster base coats as well as gypsum board and other substrates.

#### Colours

**EarthPaint** Colour Chart

#### Packaging

25kg

#### Coverage

Approximately 2.5-3kg/sqm (2 coats)

#### Solvent

Water

#### Viscosity

Paste

#### Water Vapor Permeability

Sd < 0.10m, high in accordance to UNI EN ISO 7783-2

#### Drying Time

At 25°C and 65% humidity

#### Touch Dry

2-3 hours

#### Recoat

12 hours (depending on the thickness applied)

#### VOC

Contains max 30g/L

#### Substrate Preparation

Substrate surfaces should be thoroughly cleaned and dried prior to application.

Remove all loose material and dirt, fill in defects if any with proper filler.

#### Application

Apply one coat of **EarthPaint Primer** on a well-prepared substrate. Allow primer to dry before application of **Marmorio Antico**.

With a stainless steel trowel, trowel on the first coat with pressure. In most applications, a smooth first coat is used. However, retaining irregularities in the first coat produces an effect in the finishing coat that some designers may prefer. Allow drying completely before applying the second coat.

**Recommendations**

Apply the second coat in the same manner as the first coat. Keep the trowel perpendicular to the surface to achieve the travertine marble vein effect.

For all external works, **EarthPaint Sealfix** must be applied for protection.

Do not apply if rain or freezing temperatures are expected within 24 hours; protect from rain for 48 hours after application.

Do not apply over wet or frozen surfaces. Do not apply when temperature is less than 10°C or more than 35°C.

When using multiple batches, it is recommended to remix the various products together to avoid slight differences in shading. For external applications, it is recommended to use material from the same batch from corner to corner.

**Storage & Handling**

Protect materials from direct sun. Store in dark and dry place at between 10°C and 35°C. If unopened and stored properly, the product has a shelf-life of 2 years.

Use compliant eye protection. Wear a respirator when sanding or scraping. Provide well-ventilated work areas. Avoid prolonged skin contact.

**Safety Instruction**

**EarthPaint Marmorio Antico** is not considered as dangerous according to current EU norms. The usual precautions taken when handling chemical products are recommended.

**WARNING**

*Although the information contained herein is, to the best of our knowledge and experience, true and reliable, it must be taken as merely indicative and subject to confirmation after long-term practical applications. Therefore, anyone who intends to use the product must ensure prior to usage that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product. No warranty is given or implied in connection with any recommendations or suggestions made by us or our representatives as the conditions of use and any labour involved are beyond our control.*